



Description

CS 3082 is formed in an ultra slimline design offering minimal visual impact. Easy installation can be achieved with either the supplied 'L' shaped wall brackets or the optional AC WM-CS swivel bracket, which allows the installer to angle the speaker to suit. The new CS Slimline Columns have been optimised for speech reproduction using extended range 2 inch speakers and 1 inch tweeters.

Features

- > Ideal for speech reproduction, shape designed to enable corner installation
- > Music power/RMS: 60/30W
- > Eight 50 mm (2") diameter extended range speakers and two tweeter 25 mm (1")
- \rightarrow Body in extruded aluminium bake-painted RAL 9016 White and front metal grille RAL 9016 White, includes accessory for wall mounting
- > Built-in multi-tapped transformer (30 20 10 W) for 100 V constant voltage connection
- \rightarrow 8 Ohm input that can be selected on the terminal block
- > Audio connection on screw terminal block


Part Number

13000232 CS 3082

White - RAL 9016 EAN 8024530006860



Line Art 2D



TECHNICAL SPECIFICATIONS

Acoustical specifications Frequency Res

Size

Frequency Response (-10dB) 200 Hz ÷ 20000 Hz

Max SPL @ 1m 106 dB Horizontal coverage angle 180°

Vertical coverage angle 30°
System Sensitivity 91 dB

Power sectionNominal Impedance8 ohmPower Handling30 W

Peak Power Handling 120 W PEAK

TransducersDome Tweeter2 x 1.0"Woofer8 x 2.0"

Input/Output section Input connectors Screw Terminals

Output connectors Screw Terminals

Constant Voltage Transformer 100 V

Power selection 1 30 W - 333 ohm

Power selection 2 20 W - 500 ohm

hysical specifications Cabinet/Case Material Aluminum
Hardware Wall mount bracket

Grille Steel

Color White - RAL 9016

 Height
 670 mm / 26.38 inches

 Width
 78 mm / 3.07 inches

 Depth
 66 mm / 2.6 inches

 Weight
 2.7 kg / 5.95 lbs

ACCESSORIES

Rigging / Mounting AC WM CS 13360206 8024530007614

Technical Specifications Page 2 of 2