



GTS 19G

HIGH-PERFORMANCE SUBWOOFER



Description The GTS 19G is a single 19" subwoofer module for the low-frequency extension in high-demanding touring and install applications, indoors and outdoors. Equipped with one high-excursion best-in-class transducer, it offers excellent reproduction quality and extreme sound pressure. The cabinet is provided with P-COM power connections on back panels

- Features**
- › 140 dB max SPL
 - › 19" neo woofer, 4" v.c.
 - › 2 side handles
 - › Designed to operate with XPS 16K amplifier (8 modules per amp unit)
 - › Durable and lightweight cabinet construction, polyurea coating
 - › Heavy duty, powder coated, custom perforated front grille
 - › 3 P-COM 8 pole bayonet connectors (Gold coated, CA-COM compatible, IP 68)

Part Number 13000862 GTS 19G Black EAN 8024530022082



GTS 19G

HIGH-PERFORMANCE SUBWOOFER

Acoustical specifications	Frequency Response (-10dB) Max SPL @ 1m	28 Hz ÷ 200 Hz 140 dB
Power section	Amplification Nominal Impedance LF2	Full Range 8 ohm
Transducers	Woofer	1 x 19" neo, 4.0" v.c
Input/Output section	Input connectors Output connectors	P-COM 8POLE P-COM 8POLE
Standard compliance	Safety agency	CE compliant
Physical specifications	Cabinet/Case Material Hardware Handles Pole mount/Cap Grille Color	Birch plywood M20 Socket 2 x side M20 thread Steel with clothing Black
Size	Height Width Depth Weight	531.5 mm / 20.93 inches 760 mm / 29.92 inches 655 mm / 25.79 inches 48.5 kg / 106.92 lbs

Line Art 2D

