



# MC 4064

UNIVERSAL HIGH QUALITY MICROPHONE



## Description

MC 4064 is a slim cardioid electret microphone having a flexible gooseneck. It offers impressive acoustic features and a mechanical design that is ideal for public address sound systems. This microphone has two switches (PUSH, LOCK), a red ring lamp that lights up when the microphone is activated, a high-pass filter with a switch to cut frequencies below 100 Hz. It can be mounted on tables (with or without a hole), podiums, pulpits, etc.. It can be mounted on microphone floor stands too. It has a built-in 'Phantom' power circuit; therefore, it needs to be connected to a mixer microphone input with 12 V ÷ 52 V 'Phantom' power supply.

## Features

- › Double joint gooseneck, 670 mm long
- › Installation on desks (with or without hole), lecterns, mic. floor stands
- › Buttons for stable and unstable microphone activation.
- › Red ring for active microphone indication.
- › High-pass filter with a switch to cut frequencies below 100 Hz.
- › Phantom power supply (12 ÷ 52 V)
- › 3m shielded and balanced cable with XLR connectors and 2 additional wires for command
- › Polyurethane foam windscreen

## Part Number

14115025 MC 4064

Black


EAN 8024530012014



# MC 4064

UNIVERSAL HIGH QUALITY MICROPHONE

Line Art 2D




## SCHEMATICS

MICROPHONE XLR PLUG:



BALANCED AND SHIELDED MICROPHONE CABLE WITH XLR CONNECTORS:



### Microphone specifications

#### TECHNICAL SPECIFICATIONS

Type	Electret
Directivity	Cardioid
Sensitivity	-48 dB
Frequency Response (-3dB)	100 Hz ÷ 12 kHz
Output impedance (ohm)	60.00 ohm
Phantom power	Yes
Phantom Power	12 V DC - 52 V DC

### Connections

Connectors	XLR
------------	-----

### Accessories

Cable included	Yes
Cable length (m)	3

### Standard compliance

Safety agency	CE compliant
---------------	--------------

### Physical specifications

Cabinet/Case Material	Metal
Color	Black

### Size

Height	662 mm / 26.06 inches
Diameter	21 mm / 0.83 inches