



Description

The desktop delegate microphone set MMS 3404D features a latched button to enable the microphone in mixed mode with other active MMS 3404D and MMS 3405P (if no priority button has been pressed on chairman's set). The button is completed with a LED indicator, lit when pressed. Furthermore the microphone capsule has a LED ring that is ON when the microphone is active. The 46 cm gooseneck microphone mounted on the console has a cardioid pattern, while the miniature high quality

Furthermore the microphone capsule has a LED ring that is ON when the microphone is active. The 46 cm gooseneck microphone mounted on the console has a cardioid pattern, while the miniature high quality transducer assures a good sound reinforcement in small size rooms without needing an additional sound reinforcement system. MMS 3404D are cascaded directly to one or both inputs available on MMS 3405P, by means of CAT 5FTP cable provided.

Features

- > High quality cardioid microphone
- > 46 cm gooseneck length
- > Active microphone LEDs ring
- > Push-to-lock button for mic mixed mode
- \rightarrow 1 W built in loudspeaker for sound reinforcement
- > Connection to MMS 3405P through CAT5 FTP cable
- > Robust shielded enclosure suitable for desktop or semi-flush mounting

Part Number


14322020 MMS 3404D


Grey

EAN 8024530010218



Line Art 2D





TECHNICAL SPECIFICATIONS

Microphone specifications

Туре

Electret Directivity Hypercardioid

Sensitivity 65 dB

Frequency Response (-3dB) 70 Hz ÷ 18 kHz

Console specifications Console Type Conference

Working with **FORUM 3000** LED indicators Yes

Connections RJ45 Connectors Cable FTP CAT 5

Max number in daisy-chain 79

Mixing Yes

Standard compliance Safety agency CE compliant **Physical specifications** Color Grey

Size Height 63 mm / 2.48 inches Width 170 mm / 6.69 inches 154 mm / 6.06 inches Depth

Weight $1 \, \text{kg} / 2.2 \, \text{lbs}$

Technical Specifications Page 2 of 2