

PMR 60T

TWO-WAY PENDANT MONITOR SPEAKER



Description

PMR 60T is a two-way pendant monitor speaker, suitable for a wide range of applications. Thanks to its elegant and discreet design and refined finishes, it is suitable for all environmental and architectural conditions. Featuring a 6.5" woofer and 80 W RMS power, it is also equipped with a transformer for connection to constant voltage lines (70/100 V). The high quality of its transducers (arranged in a coaxial configuration) guarantees faithful and precise musical reproduction throughout the audio spectrum and allows to reach truly remarkable sound pressure levels for such compact products. The connection is simple and safe thanks to the removable four-pole screw terminals. The front grille is fixed by magnets and can therefore be easily removed to access the power rotary switch.

Features

- > 80W RMS power handling
- > 114 dB max SPL
- > 70 ÷ 20000 Hz frequency range
- > 130° constant directivity conical coverage angle
- > 6.5" high power woofer
- > 1" neodymium dome tweeter
- > Self extinguishing plastic body
- > Steel magnetic front grille
- > 4 pole EUROBLOCK connector (audio input and parallel link output)
- > 5 m hanging cable included

Part Number


13100098 PMR 60T W 13100100 PMR 60T B White - RAL 9003 EAN 8024530020606 Black - RAL 9005 EAN 8024530020590



PMR 60T


TWO-WAY PENDANT MONITOR SPEAKER

Line Art 2D













TECHNICAL SPECIFICATIONS

Acoustical specifications

Power section

Size

Frequency Response (-10dB) 70 Hz ÷ 20000 Hz

Max SPL @ 1m114 dBCoverage angle130°System Sensitivity89 dBAmplificationFull Range

Nominal Impedance8 ohmPower Handling80 W RMSPeak Power Handling320 W PEAKCrossover Frequencies2500 Hz

Recommended Amplifiers DMA 504, DMA 162, DMA 82, DMA 162P

TransducersDome Tweeter1 x 1.0" neo, 1.0" v.cWoofer1 x 6.5", 1.2" v.c

Input/Output section Input connectors Euroblock

Output connectors Euroblock
Constant Voltage Transformer 70/100 V
Power selection 1 80 W - 125 ohm
Power selection 2 40 W - 250 ohm

 Power selection 2
 40 W - 250 ohm

 Power selection 3
 20 W - 500 ohm

 Power selection 4
 10 W - 1000 ohm

 Power selection 5
 5 W - 2000 ohm

 Standard compliance
 Safety agency
 CE compliant

 Physical specifications
 Cabinet/Case Material
 ABS

Grille Steel
Color White - RAL 9003, Black - RAL 9005

 $\begin{array}{lll} \mbox{Height} & 236\mbox{ mm} \,/\, 9.29\mbox{ inches} \\ \mbox{Diameter} & 300\mbox{ mm} \,/\, 11.81\mbox{ inches} \\ \mbox{Weight} & 5.1\mbox{ kg} \,/\, 11.24\mbox{ lbs} \end{array}$

Technical Specifications Page 2 of 2