

PR 4093

9 INPUTS, 3 OUTPUTS PREAMPLIFIER



Description

PR 4093 has been designed to provide a flexible solution for paging and music application in PA systems. It offers 6 balanced inputs mic/line with PHANTOM facility, the first of them with priority triggered by VOX circuit. In addition, 3 stereo input on RCA connectors are available. Outputs offer different functionalities, included tone control on front panel, dedicated mixing of inputs 1-6 e connection to recording devices.

Features

- > 6balanced XLR inputs with MIC/LINE sensibility and selectable PHANTOM power
- > 3 stereo inputs on RCA connectors
- > SIGNAL presence LED for each input
- > Priority function on input 1, activatable through VOX circuit
- > 1 XLR stereo output with tone control LOW, MID, HIGH on front panel
- \rightarrow 1 MONO output on $1\!\!\!/4''$ jack connnector
- > 1 MIC output on 1/4" jack connnector
- > Connection to recording device on RCA connectors
- > LED output level indicator
- > 230V AC functioning and 24V DC emergency power supply

Part Number


17100003 PR 4093 17100007 PR 4093 220-240 V Black 115 V Black EAN 8024530013677 EAN 8024530015367



PR 4093

9 INPUTS, 3 OUTPUTS PREAMPLIFIER

Line Art 2D







TECHNICAL SPECIFICATIONS

Audio performance	Frequency Response (-3dB)	20 Hz ÷ 22 kHz
	Crosstalk (on the whole bandwitch)	<-68 dB

Distortion (THD+N) @ 1 kHz nominal power <0.03 %

Input sectionTotal number of inputs9Balanced6

Unbalanced 3
Mono 6
Stereo 3
Line inputs 3
Line connectors RCA
Mic+Line inputs 6

Mic+Line connectors XLR
Mic+Line Phantom 18 V DC - 21 V DC

VOX Yes

Output sectionSignal output number3

Signal output connectors JACK, RCA, XLR

Processing Tone controls Yes

ControlsConfigurationFront panelProtectionsCoolingConvection

Power requirement Operating voltage 220-240/115 V~ 50/60Hz

Voltage selection Internal
DC power Yes
DC power value 24 V
Power consumption 18 W

Standard compliance | Safety agency | CE compliant

Physical specifications | Cabinet/Case Material | Metal

Color Black
Rack mounting 19", 1U

Technical Specifications Page 2 of 3



PR 4093

9 INPUTS, 3 OUTPUTS PREAMPLIFIER

Size

Height Width Depth Weight 44 mm / 1.73 inches 483 mm / 19.02 inches 195 mm / 7.68 inches 2.8 kg / 6.17 lbs

Technical Specifications Page 3 of 3